

## SUBMERSIBLE PUMP

### SUBMERSIBLE BOREHOLE MULTISTAGE PUMP

**S4S-5-100M | S4S-8-150M | S4S-10-200M | S4S-15-300M**

**S4S-11-100R | S4S-12-150R | S4S-15-200R | S4S-28-300R**

#### PRODUCT DESCRIPTION

Pumping ground water from bore wells for Agriculture, Irrigation, Water Treatment plants, Domestic and Industry application.

Pump & Motor Casing : SS      Insulation Class : F      Protection : IP68  
 Motor Winding : Copper      Impeller : P.C      Outer Diameter : 100 MM  
 Shaft : AISI304 SS      Mechanical Seal : Ceramic/ Graphite

Maximum content of Solid Substance : 40g/m<sup>3</sup>      Provided with SS Check Valve and sand proof cover



TECH. FEATURES	S4S-5-100M	S4S-8-150M	S4S-10-200M	S4S-15-300M
Power	0.75 kW / 1 HP	1.1 kW / 1.5 HP	1.5 kW / 2 HP	2.2 kW / 3 HP
Voltage	220 V- 240 V	220 V- 240 V	220 V- 240 V	220 V- 240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Capacitor	40 µf	45 µf	65 µf	80 µf
RPM	2850	2850	2850	2850
Max Head	30 Meter	50 Meter	60 Meter	90 Meter
Max Discharge	200 l/min	200 l/min	200 l/min	200 l/min
Cable	4 Corex0.75 Sqmm	4 Corex1 Sqmm	4 Corex1.5 Sqmm	4 Corex2 Sqmm
Cable Length	15 Meter	20 Meter	25 Meter	30 Meter
Outlet	2"	2"	2"	2"

TECH. FEATURES	S4S-11-100R	S4S-12-150R	S4S-15-200R	S4S-28-300R
Power	0.75 kW / 1 HP	1.1 kW / 1.5 HP	1.5 kW / 2HP	2.2 kW / 3 HP
Voltage	220 V- 240 V	220 V- 240 V	220 V- 240 V	220 V- 240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Capacitor	40 µf	45 µf	65 µf	80 µf
RPM	2850	2850	2850	2850
Max Head	70 Meter	70 Meter	90 Meter	180 Meter
Max Discharge	85 l/min	135 l/min	135 l/min	85 l/min
Cable	4 Corex0.75 Sqmm	4 Corex1 Sqmm	4 Corex1.5 Sqmm	4 Corex2 Sqmm
Cable Length	15 Meter	20 Meter	25 Meter	30 Meter
Outlet	1.25"	1.25"	1.25"	1.25"

**UAE • OMAN • QATAR • BAHRAIN • KUWAIT**

